

Art.: 8147,8148,8149,8042,8042B,8145,8043,8044,8640
8045,8440,8441,8442,8540,8144,8144B,8041,8641

swedbe

Kitchen&Drinking Faucet.Installation Guide

Technical characteristics

The maximum working pressure

0,63 MPa
(6.5 bar)

The filtered water temperature

(95.5 psi)
+4 to +38 °C
(39 to 100 °F)

The no filtered water temperature

to +75 °C
(to +167 °F)

Maintenance tips

*Clean periodically with soap & water using a soft cloth.

*For better protection of the product surface, usage of strong detergents or any other corrosive solvents should be avoided.

*In the event your tapwater has higher harder or mineral contents immediate cleaning of the faucet aerator is recommended to protect from calcium or other mineral corrosion.

Manufacturer`s warranty

Term storage faucet before - 3 years at a temperature range of +5 to +38 °C (41 °F - 104 °F), without disturbing the packaging.

Beauty filtered & regular kitchen faucet

*Innovated Design: Free-trouble to drilling another hole for drinking faucet next to regular kitchen faucet on sink.

*Tap Water & Drinking water source from this dual-using kitchen faucet; but there is a concealed waterway to separate drinking water from spout. It`s absolute safety / convenient / saving space design.

